PT1RUE

TOUCH SCREEN LCD DISPLAY

Panel Type	10.4” TFT Active Matrix Panel
Max. Resolution	800×600 SVGA
Pixel Pitch	0.264 (H) × 0.264 (V)
Contrast Ratio	500:1
Brightness	230 cd/m2
Display Area	211.2 × 158.4 mm
Response Time	35 ms (Typ.)
Display Colors	262K
Viewing Angle	120°(H)/100°(V)
Signal Connector	VGA
VGA Input Signal	RGB Analog 0.7V Peak to Peak
OSD Control	Power Switch, Menu, Select (+, -), Auto
Operation Temperature	0° ~ 50° C
Storage Temperature	-20° ~ 60° C
Power Consumption	25 W
Power Supply	External Power Adapter
Safely & EMI	CE, FCC, TUV-GS, UL Compliant
Touch screen	Resistive; USB
Mounting	VESA 75 mm; Table Mount
Dimension	(With Stand) 274.62 x 245.23 x 153.54(mm) 10.82” x 9.65” x 6.05” (Without Stand) 274.62 x 201.62 x 48.95 (mm) 10.82” x 7.94” x 1.93”
Weight	4.75 lbs (2.1 kg)

ACCUVIEW INC•
Tel: 800.275.4255 Fax: 201.440.5655 Address: 40C Cotters Lane, Suite F, East Brunswick NJ 08816 Email: sales@accuview.com
*Specifications subject to change without notice. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 Accuview Inc. All rights reserved.

WWW.ACCUVIEW.COM

Rev. 07/12